

MEGUIAR'S D120 - DETAILER GLASS CLEANER CONCENTRATE

ChemWatch Material Safety Data Sheet
Issue Date: Tue 15-Mar-2005

CHEMWATCH 4827-27
CD 2005/1 Page 1 of 14

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

MEGUIAR'S D120 - DETAILER GLASS CLEANER CONCENTRATE

SYNONYMS

Manufacturer's Code: D120

PROPER SHIPPING NAME

FLAMMABLE LIQUID, N.O.S. (contains isopropanol)

PRODUCT USE

Glass cleaner.

SUPPLIER

Company: Meguiar's Australia P/L

Address:

35 Slough Business Park

Holker St, Silverwater

NSW, 2128

AUSTRALIA

Telephone: (+61 2) 9737 9422

Telephone: 1800 804 182

Fax: 02 9737 9414

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS.

According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

S6

RISK

Flammable.

May form explosive peroxides.

Harmful by inhalation, in contact with skin and if swallowed.

Irritating to eyes, respiratory system and skin.

Limited evidence of a carcinogenic effect.

HARMFUL-May cause lung damage if swallowed.

Vapours may cause drowsiness and dizziness.

SAFETY

Keep away from sources of ignition. No smoking.

Keep container in a well ventilated place.

Avoid exposure - obtain special instructions before use.

Do not empty into drains.

Keep container tightly closed.

Take off immediately all contaminated clothing.

In case of contact with eyes, rinse with plenty of water and contact Doctor or

continued...

MEGUIAR'S D120 - DETAILER GLASS CLEANER CONCENTRATE

ChemWatch Material Safety Data Sheet
Issue Date: Tue 15-Mar-2005

CHEMWATCH 4827-27
CD 2005/1 Page 2 of 14

Section 2 - HAZARDS IDENTIFICATION

Poisons Information Centre.

If you feel unwell contact Doctor or Poisons Information Centre. (Show the label if possible).

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
ethylene glycol monobutyl ether	111-76-2	15-30
isopropanol	67-63-0	15-30

Section 4 - FIRST AID MEASURES

SWALLOWED

• IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.

- For advice, contact a Poisons Information Centre or a doctor.
- Where Medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:
- For advice, contact a Poisons Information Centre or a doctor.
- Urgent hospital treatment is likely to be needed.
- If conscious, give water to drink.
- INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

NOTE: Wear a protective glove when inducing vomiting by mechanical means.

- In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.
- If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the MSDS should be provided. Further action will be the responsibility of the medical specialist.
- If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the MSDS.

EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.

continued...

MEGUIAR'S D120 - DETAILER GLASS CLEANER CONCENTRATE

ChemWatch Material Safety Data Sheet
Issue Date: Tue 15-Mar-2005

CHEMWATCH 4827-27
CD 2005/1 Page 3 of 14
Section 4 - FIRST AID MEASURES

- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

Followed acute or short term repeated exposures to ethylene glycol monoalkyl ethers and their acetates:

- Hepatic metabolism produces ethylene glycol as a metabolite.
- Clinical presentation, following severe intoxication, resembles that of ethylene glycol exposures.
- Monitoring the urinary excretion of the alkoxyacetic acid metabolites may be a useful indication of exposure.

[Ellenhorn and Barceloux: Medical Toxicology]

For acute or short term repeated exposures to ethylene glycol:

- Early treatment of ingestion is important. Ensure emesis is satisfactory.
- Test and correct for metabolic acidosis and hypocalcaemia.
- Apply sustained diuresis when possible with hypertonic mannitol.
- Evaluate renal status and begin haemodialysis if indicated. [I.L.O]
- Rapid absorption is an indication that emesis or lavage is effective only in the first few hours. Cathartics and charcoal are generally not effective.
- Correct acidosis, fluid/electrolyte balance and respiratory depression in the usual manner. Systemic acidosis (below 7.2) can be treated with intravenous sodium bicarbonate solution.
- Ethanol therapy prolongs the half-life of ethylene glycol and reduces the formation of toxic metabolites.
- Pyridoxine and thiamine are cofactors for ethylene glycol metabolism and should be given (50 to 100 mg respectively) intramuscularly, four times per day for 2 days.
- Magnesium is also a cofactor and should be replenished. The status of 4-methylpyrazole, in the treatment regime, is still uncertain. For clearance of the material and its metabolites, haemodialysis is much superior to peritoneal dialysis.

[Ellenhorn and Barceloux: Medical Toxicology]

It has been suggested that there is a need for establishing a new biological exposure limit before a workshift that is clearly below 100 mmol ethoxy-acetic acids per mole creatinine in morning urine of people occupationally exposed to ethylene glycol ethers. This arises from the finding that an increase in urinary stones may be associated with such exposures.

Laitinen J., et al: Occupational & Environmental Medicine 1996; 53, 595-600

For acute or short term repeated exposures to isopropanol:

- Rapid onset respiratory depression and hypotension indicates serious ingestions that require careful cardiac and respiratory monitoring together with immediate intravenous access.
- Rapid absorption precludes the usefulness of emesis or lavage 2 hours post-ingestion. Activated charcoal and cathartics are not clinically useful. Ipecac is most useful when given 30 mins. post-ingestion.
- There are no antidotes.
- Management is supportive. Treat hypotension with fluids followed by vasopressors.
- Watch closely, within the first few hours for respiratory depression; follow arterial blood gases and tidal volumes.
- Ice water lavage and serial haemoglobin levels are indicated for those patients with evidence of gastrointestinal bleeding.

continued...

MEGUIAR'S D120 - DETAILER GLASS CLEANER CONCENTRATE

ChemWatch Material Safety Data Sheet
Issue Date: Tue 15-Mar-2005

CHEMWATCH 4827-27
CD 2005/1 Page 4 of 14

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 500 metres in all directions.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are flammable.
- Moderate fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Moderate explosion hazard when exposed to heat or flame.
- Vapour may travel a considerable distance to source of ignition.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include
carbon dioxide (CO₂)

other pyrolysis products typical of burning organic material

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

HAZCHEM

3[Y]

Personal Protective Equipment

PERSONAL PROTECTION EQUIPMENT

Breathing apparatus.
Chemical splash suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

continued...

MEGUIAR'S D120 - DETAILER GLASS CLEANER CONCENTRATE

ChemWatch Material Safety Data Sheet
Issue Date: Tue 15-Mar-2005

CHEMWATCH 4827-27
CD 2005/1 Page 5 of 14

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Wipe up.
- Collect residues in a flammable waste container.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse / absorb vapour.
- Contain spill with sand, earth or vermiculite.
- Use only spark-free shovels and explosion proof equipment.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

PROTECTIVE ACTIONS FOR SPILL

COULD NOT FIND
ISOPAZON.WMF

From IERG (Canada/Australia)

Isolation Distance	25 metres
Downwind Protection Distance	300 metres
IERG Number	14

FOOTNOTES

- 1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapour plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.
- 2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with

continued...

MEGUIAR'S D120 - DETAILER GLASS CLEANER CONCENTRATE

ChemWatch Material Safety Data Sheet
Issue Date: Tue 15-Mar-2005

CHEMWATCH 4827-27
CD 2005/1 Page 6 of 14

Section 6 - ACCIDENTAL RELEASE MEASURES

those closest to the spill and working away from the site in the downwind direction. Within the protective action zone a level of vapour concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.

- 3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localised wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.
- 4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also considered "small spills".
LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.
- 5 Guide 128 is taken from the US DOT emergency response guide book.
- 6 IERG information is derived from CANUTEC - Transport Canada.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

DO NOT allow clothing wet with material to stay in contact with skin

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of overexposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid generation of static electricity.
- DO NOT use plastic buckets.
- Earth all lines and equipment.
- Use spark-free tools when handling.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

SUITABLE CONTAINER

DO NOT use aluminium or galvanised containers

Packing as supplied by manufacturer. Plastic containers may only be used if approved for flammable liquid. Check that containers are clearly labelled and free from leaks.

- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.

continued...

MEGUIAR'S D120 - DETAILER GLASS CLEANER CONCENTRATE

ChemWatch Material Safety Data Sheet
Issue Date: Tue 15-Mar-2005

CHEMWATCH 4827-27
CD 2005/1 Page 7 of 14

Section 7 - HANDLING AND STORAGE

- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C)
 - (i) : Removable head packaging;
 - (ii) : Cans with friction closures and
 - (iii) : low pressure tubes and cartridges may be used.
- Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages
- In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

STORAGE INCOMPATIBILITY

Glycol ethers may form peroxides under certain conditions. In the presence of strong bases or the salts of strong bases, at elevated temperatures, the potential exists for runaway reactions. Contact with aluminium should be avoided. Release of hydrogen gas may result.
Avoid reaction with oxidising agents

STORAGE REQUIREMENTS

- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed.
- Store away from incompatible materials in a cool, dry, well-ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³
Australian Exposure Standards	2-Butoxyethanol	25	121				
Australian Exposure Standards	Isopropyl alcohol	400	983	500	1,230		

ODOUR SAFETY FACTOR (OSF)

OSF=2E2 (2-BUTOXY ETHANOL)

Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class A or B.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
-------	-----	-------------

continued...

MEGUIAR'S D120 - DETAILER GLASS CLEANER CONCENTRATE

ChemWatch Material Safety Data Sheet
Issue Date: Tue 15-Mar-2005

CHEMWATCH 4827-27
CD 2005/1 Page 8 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV-TWA for example) is being reached, even when distracted by working activities
B	26-550	As "A" for 50-90% of persons being distracted
C	1-26	As "A" for less than 50% of persons being distracted
D	0.18-1	10-50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As "D" for less than 10% of persons aware of being tested

REPRODUCTIVE HEALTH GUIDELINES

Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits.

Ingredient	ORG	UF	Endpoint	CR	TLV Adeq
ethylene glycol mono	3.6 mg/m ³	100	D	NA	-

These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

D = Developmental; R = Reproductive; TC = Transplacental carcinogen

Jankovic J., Drake F.: A Screening Method for Occupational Reproductive

American Industrial Hygiene Association Journal 57: 641-649 (1996)

INGREDIENT DATA

ETHYLENE GLYCOL MONOBUTYL ETHER:

TLV TWA: 20 ppm A3 [ACGIH]

PEL TWA: 50 ppm, 240 mg/m³ (SKIN) [OSHA Z1]

TLV TWA: 20 ppm A3

CAUTION: This substance has been classified by the ACGIH as A3 Animal Carcinogen (at relatively high doses)

ES TWA: 25 ppm, 121 mg/m³ (skin) Under review

OES TWA: 25 ppm, 123 mg/m³ (skin)

Exposure limits with "skin" notation indicate that vapour and liquid may be

continued...

MEGUIAR'S D120 - DETAILER GLASS CLEANER CONCENTRATE

ChemWatch Material Safety Data Sheet
Issue Date: Tue 15-Mar-2005

CHEMWATCH 4827-27
CD 2005/1 Page 9 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

MAK value: 20 ppm, 98 mg/m³

Designated H in List of MAK values: Danger of cutaneous absorption.

Absorption of such substances through the skin can pose an incomparably larger danger of toxicity than their inhalation. To avoid health risks when handling such substances, meticulous cleaning of the skin, hair and clothing is imperative.

MAK Category II Peak Limitation: For substances with systemic effects and with a half-life in humans of less than two hours.

Allows excursions of 2 times the MAK value, for 30 minutes (on average), four times per shift.

MAK Group C: There is no reason to fear risk of damage to the developing embryo when MAK and BAT values are observed.

MAK values, and categories and groups are those recommended within the Federal Republic of Germany

Odour Threshold Value: 0.10 ppm (detection), 0.35 ppm (recognition)

IDLH Level: 700 ppm

Although rats appear to be more susceptible than other animals anaemia is not uncommon amongst humans following exposure. The TLV reflects the need to maintain exposures below levels found to cause blood changes in experimental animals. It is concluded that this limit will reduce the significant risk of irritation, haematologic effects and other systemic effects observed in humans and animals exposed to higher vapour concentrations. The toxic effects typical of some other glycol ethers (pancytopenia, testis atrophy and teratogenic effects) are not found with this substance.

ISOPROPANOL:

NOTICE OF INTENDED CHANGE

TLV TWA: 400 ppm [ACGIH]

TLV STEL: NOTICE OF INTENDED CHANGE 500 ppm [ACGIH]

TLV TWA: 200 ppm A4 [ACGIH]

TLV STEL: 400 ppm A4 [ACGIH]

PEL TWA: 400 ppm, 980 mg/m³ [OSHA Z1]

TLV TWA: 200 ppm; STEL: 400 ppm A4

NOTE: This substance has been classified by the ACGIH as A4 NOT classifiable as causing Cancer in humans

ES TWA: 400 ppm, 980 mg/m³; STEL: 500 ppm, 1225 mg/m³ (Under review)

OES TWA: 400 ppm, 999 mg/m³; STEL: 500 ppm, 1250 mg/m³

MAK value: 200 ppm, 500 mg/m³

MAK Category II Peak Limitation: For substances with systemic effects and with a half-life in humans of less than two hours.

Allows excursions of 2 times the MAK value, for 30 minutes (on average), four times per shift.

MAK Group C: There is no reason to fear risk of damage to the developing embryo when MAK and BAT values are observed.

MAK values, and categories and groups are those recommended within the Federal Republic of Germany

IDLH Level: 2000 ppm (lower explosive limit)

Odour Threshold Value: 3.3 ppm (detection), 7.6 ppm (recognition)

Exposure at or below the recommended TLV-TWA and STEL is thought to minimise the potential for inducing narcotic effects or significant irritation of the eyes or upper respiratory tract. It is believed, in the

continued...

MEGUIAR'S D120 - DETAILER GLASS CLEANER CONCENTRATE

ChemWatch Material Safety Data Sheet
Issue Date: Tue 15-Mar-2005

CHEMWATCH 4827-27
CD 2005/1 Page 10 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

absence of hard evidence, that this limit also provides protection against the development of chronic health effects. The limit is intermediate to that set for ethanol, which is less toxic, and n-propyl alcohol, which is more toxic, than isopropanol.

PERSONAL PROTECTION

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them. DO NOT wear contact lenses.

HANDS/FEET

Wear chemical protective gloves, eg. PVC.
Wear safety footwear or safety gumboots, eg. Rubber

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the: "Forsberg Clothing Performance Index".
The effect(s) of the following substance(s) are taken into account in the computer-generated selection:

Substance

ethylene glycol monobutyl ether	
isopropanol	
PE/EVAL/PE	A
NITRILE	A
NEOPRENE	B
PVC	B
NAT+NEOPR+NITRILE	C
NATURAL RUBBER	C

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

continued...

MEGUIAR'S D120 - DETAILER GLASS CLEANER CONCENTRATE

ChemWatch Material Safety Data Sheet
Issue Date: Tue 15-Mar-2005

CHEMWATCH 4827-27
CD 2005/1 Page 11 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Dark blue flammable liquid with a characteristic odour; mixes with water.

PHYSICAL PROPERTIES

Mixes with water.

Molecular Weight: Not Applicable

Melting Range (°C): Not Available

Solubility in water (g/L): Miscible

pH (1% solution): Not Available

Volatile Component (%vol): Not Available

Relative Vapour Density (air=1): 3.07

Lower Explosive Limit (%): 2.5 (isopropanol)

Autoignition Temp (°C): Not Available

State: LIQUID

Boiling Range (°C): 82

Specific Gravity (water=1): 0.89

pH (as supplied): 7.5

Vapour Pressure (kPa): 4.4 @ 20C (isopropanol)

Evaporation Rate: 2 BuAC = 1

Flash Point (°C): 29.3 (PMCC)

Upper Explosive Limit (%): 12 (isopropanol)

Decomposition Temp (°C): Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
 - Product is considered stable.
 - Hazardous polymerisation will not occur.
-

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

Overexposure to non-ring alcohols causes nervous system symptoms. These include headache, muscle weakness and inco-ordination, giddiness, confusion, delirium and coma. Digestive symptoms may include nausea, vomiting and diarrhoea.

Aspiration is much more dangerous than ingestion because lung damage can occur and the substance is absorbed into the body. Alcohols with ring structures and secondary and tertiary alcohols cause more severe symptoms, as do heavier alcohols.

EYE

There is evidence that material may produce eye irritation in some persons and

continued...

MEGUIAR'S D120 - DETAILER GLASS CLEANER CONCENTRATE

ChemWatch Material Safety Data Sheet
Issue Date: Tue 15-Mar-2005

CHEMWATCH 4827-27
CD 2005/1 Page 12 of 14

Section 11 - TOXICOLOGICAL INFORMATION

produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain. There may be damage to the cornea. Unless treatment is prompt and adequate there may be permanent loss of vision. Conjunctivitis can occur following repeated exposure.

The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflammation, ulceration

SKIN

Skin contact with the material may be harmful; systemic effects may result following absorption.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

INHALED

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.

The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, drowsiness, reduced alertness, loss of reflexes, lack of coordination and vertigo.

If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.

Acute effects from inhalation of high vapour concentrations may be chest and nasal irritation with coughing, sneezing, headache and even nausea.

CHRONIC HEALTH EFFECTS

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There is some evidence that human exposure to the material may result in developmental toxicity. This evidence is based on animal studies where effects have been observed in the absence of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not secondary non-specific consequences of the other toxic effects. Ethylene glycol esters and their ethers cause wasting of the testicles, reproductive changes, infertility and changes to kidney function. Shorter chain compounds are more dangerous. They are also associated with the formation of stones in the urine.

Meguiar's D120 - Detailer Glass Cleaner Concentrate

Not available. Refer to individual constituents.

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

ETHYLENE GLYCOL MONOBUTYL ETHER: TOXICITY

Oral (rat) LD50: 470 mg/kg

Dermal (rabbit) LD50: 220 mg/kg

Inhalation (human) TClO: 100 ppm

Inhalation (human) TClO: 195 ppm/8h

Inhalation (rat-male) LC50: 486 ppm *

Inhalation (rat-female) LC50: 450 ppm *

NOTE: Changes in kidney, liver, spleen and lungs are observed in animals

IRRITATION

Skin (rabbit): 500 mg, open; mild

Eye (rabbit): 100 mg/24h-moderate

Eye (rabbit): 100 mg SEVERE

* [Union Carbide]

continued...

MEGUIAR'S D120 - DETAILER GLASS CLEANER CONCENTRATE

ChemWatch Material Safety Data Sheet
Issue Date: Tue 15-Mar-2005

CHEMWATCH 4827-27
CD 2005/1 Page 13 of 14

Section 11 - TOXICOLOGICAL INFORMATION

exposed to high concentrations of this substance by all routes.

ISOPROPANOL:

TOXICITY

Oral (human) LDLo: 3570 mg/kg

Oral (human) TDLo: 223 mg/kg

Oral (man) TDLo: 14432 mg/kg

Oral (rat) LD50: 5045 mg/kg

Dermal (rabbit) LD50: 12800 mg/kg

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

IRRITATION

Skin (rabbit): 500 mg - mild

Eye (rabbit): 10 mg - moderate

Eye (rabbit): 100mg/24hr-moderate

Eye (rabbit): 100 mg - SEVERE

Section 12 - ECOLOGICAL INFORMATION

DO NOT discharge into sewer or waterways.

Section 13 - DISPOSAL CONSIDERATIONS

Puncture containers to prevent re-use and bury at an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION



Shipping Name:

FLAMMABLE LIQUID, N.O.S.

(contains isopropanol)

Dangerous Goods Class: 3

UN/NA Number: 1993

ADR Number: 30

Packing Group: III

Labels Required: flammable liquid

Additional Shipping Information:

International Transport Regulations:

IMO: 3

HAZCHEM

3[Y]

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE

S6

continued...

MEGUIAR'S D120 - DETAILER GLASS CLEANER CONCENTRATE

ChemWatch Material Safety Data Sheet
Issue Date: Tue 15-Mar-2005

CHEMWATCH 4827-27
CD 2005/1 Page 14 of 14

Section 15 - REGULATORY INFORMATION

REGULATIONS

ethylene glycol monobutyl ether (CAS: 111-76-2) is found on the following regulatory lists:

- Australian Inventory of Chemical Substances (AICS)
- Australian Poisons Schedule

isopropanol (CAS: 67-63-0) is found on the following regulatory lists:

- Australian Inventory of Chemical Substances (AICS)

Section 16 - OTHER INFORMATION

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Tue 15-Mar-2005

Print Date: Wed 16-Mar-2005