

# Meguiar's G41 - Natural Shine

## MOTORACTIVE

Chemwatch: 4910-95  
Version No: 8.1.1.1  
Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 2

Issue Date: 06/03/2015  
Print Date: 05/09/2016  
S.GHS.AUS.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

|                               |                               |
|-------------------------------|-------------------------------|
| Product name                  | Meguiar's G41 - Natural Shine |
| Synonyms                      | Reference number: 18-95D      |
| Other means of identification | Not Available                 |

### Relevant identified uses of the substance or mixture and uses advised against

|                          |  |
|--------------------------|--|
| Relevant identified uses | Protective coating, maintenance product. |
|--------------------------|--|

### Details of the supplier of the safety data sheet

|                         |   |
|-------------------------|---|
| Registered company name | MOTORACTIVE   |
| Address                 | Unit 35, Slough Business Park, Holker Street Silverwater NSW 2128 Australia |
| Telephone               | (02) 9737 9422  |
| Fax                     | (02) 9737 9414  |
| Website                 | www.motoractive.com.au  |
| Email                   | Not Available   |

### Emergency telephone number

|                                   |   |
|-----------------------------------|---|
| Association / Organisation        | MotorActive   |
| Emergency telephone numbers       | +61 2 9737 9422 (For General Information Monday to Friday 8:30am to 5:pm) |
| Other emergency telephone numbers | 13 11 26 (In Case of Emergency contact: Poison Information Hotline)       |

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture

**HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.**

### CHEMWATCH HAZARD RATINGS

|              | Min | Max |              |
|--------------|-----|-----|--------------|
| Flammability | 1   |     |              |
| Toxicity     | 0   |     | 0 = Minimum  |
| Body Contact | 2   |     | 1 = Low      |
| Reactivity   | 1   |     | 2 = Moderate |
| Chronic      | 0   |     | 3 = High     |
|              |     |     | 4 = Extreme  |

|                    |   |
|--------------------|---|
| Poisons Schedule   | S5  |
| Classification [1] | Eye Irritation Category 2A, Specific target organ toxicity - single exposure Category 3 (narcotic effects)                    |
| Legend:            | 1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI |

### Label elements

|                    |   |
|--------------------|---|
| GHS label elements |  |
| SIGNAL WORD        | WARNING   |

### Hazard statement(s)

|      |                                    |
|------|------------------------------------|
| H319 | Causes serious eye irritation.     |
| H336 | May cause drowsiness or dizziness. |

### Supplementary statement(s)

Not Applicable

### CLP classification (additional)

Not Applicable

### Precautionary statement(s) Prevention

|      |   |
|------|---|
| P271 | Use only outdoors or in a well-ventilated area. |
|------|---|

|      |  |
|------|--|
| P261 | Avoid breathing mist/vapours/spray.  |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |

#### Precautionary statement(s) Response

|                |  |
|----------------|--|
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P312           | Call a POISON CENTER or doctor/physician if you feel unwell.   |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P304+P340      | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.                                 |

#### Precautionary statement(s) Storage

|           |  |
|-----------|--|
| P405      | Store locked up.   |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |

#### Precautionary statement(s) Disposal

|      |   |
|------|---|
| P501 | Dispose of contents/container in accordance with local regulations. |
|------|---|

### SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

#### Substances

See section below for composition of Mixtures

#### Mixtures

| CAS No    | %[weight] | Name                          |
|-----------|-----------|-------------------------------|
| 577-11-7  | 1-5       | sodium dioctyl sulfosuccinate |
| 9007-48-1 | 1-5       | polyglycerol oleate           |

### SECTION 4 FIRST AID MEASURES

#### Description of first aid measures

|              |   |
|--------------|---|
| Eye Contact  | <p>If this product comes in contact with the eyes:<br/>Wash out immediately with fresh running water.<br/>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.<br/>Seek medical attention without delay; if pain persists or recurs seek medical attention.<br/>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</p>  |
| Skin Contact | <p>If skin contact occurs:<br/>Immediately remove all contaminated clothing, including footwear.<br/>Flush skin and hair with running water (and soap if available).<br/>Seek medical attention in event of irritation.</p>   |
| Inhalation   | <p>If fumes or combustion products are inhaled remove from contaminated area.<br/>Lay patient down. Keep warm and rested.<br/>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.<br/>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained.<br/>Perform CPR if necessary.<br/>Transport to hospital, or doctor.</p>  |
| Ingestion    | <p><b>If swallowed do NOT induce vomiting.</b><br/>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.<br/>Observe the patient carefully.<br/>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.<br/>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.<br/>Seek medical advice.<br/>Avoid giving milk or oils.<br/>Avoid giving alcohol.</p> |

#### Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.

Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> 50 mm Hg) should be intubated.

Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.

A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.

Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.

Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology] Treat symptomatically.

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.

In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.

High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

**NOTE:** Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

### SECTION 5 FIREFIGHTING MEASURES

#### Extinguishing media

Water spray or fog.

Alcohol stable foam.  
Dry chemical powder.  
Carbon dioxide.

### Special hazards arising from the substrate or mixture

|                                |   |
|--------------------------------|---|
| <b>Fire Incompatibility</b>    | Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result  |
| <b>Advice for firefighters</b> |   |
| <b>Fire Fighting</b>           | Alert Fire Brigade and tell them location and nature of hazard.<br>Wear full body protective clothing with breathing apparatus.<br>Prevent, by any means available, spillage from entering drains or water course.<br>Use water delivered as a fine spray to control fire and cool adjacent area.   |
| <b>Fire/Explosion Hazard</b>   | Combustible.<br>Slight fire hazard when exposed to heat or flame.<br>Heating may cause expansion or decomposition leading to violent rupture of containers.<br>On combustion, may emit toxic fumes of carbon monoxide (CO).<br>Combustion products include:carbon dioxide (CO2) silicon dioxide (SiO2) other pyrolysis products typical of burning organic materialMay emit poisonous fumes. <b>CARE:</b> Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire. |
| <b>HAZCHEM</b>                 | Not Applicable  |

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

|                     |   |
|---------------------|---|
| <b>Minor Spills</b> | Remove all ignition sources.<br>Clean up all spills immediately.<br>Avoid breathing vapours and contact with skin and eyes.<br>Control personal contact with the substance, by using protective equipment.  |
| <b>Major Spills</b> | Silicone fluids, even in small quantities, may present a slip hazard.<br>It may be necessary to rope off area and place warning signs around perimeter.<br>Clean up area from spill, with suitable absorbant, as soon as practically possible.<br>Final cleaning may require use of steam, solvents or detergents.<br>Moderate hazard.<br>Clear area of personnel and move upwind.<br>Alert Fire Brigade and tell them location and nature of hazard.<br>Wear breathing apparatus plus protective gloves. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

|                          |  |
|--------------------------|--|
| <b>Safe handling</b>     | Containers, even those that have been emptied, may contain explosive vapours.<br>Do NOT cut, drill, grind, weld or perform similar operations on or near containers.<br><b>DO NOT allow clothing wet with material to stay in contact with skin</b><br>Electrostatic discharge may be generated during pumping - this may result in fire.<br>Ensure electrical continuity by bonding and grounding (earthing) all equipment.<br>Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$ m/sec until fill pipe submerged to twice its diameter, then $\leq 7$ m/sec).<br>Avoid splash filling.<br>Avoid all personal contact, including inhalation.<br>Wear protective clothing when risk of exposure occurs.<br>Use in a well-ventilated area.<br>Prevent concentration in hollows and sumps. |
| <b>Other information</b> | Store in original containers.<br>Keep containers securely sealed.<br>No smoking, naked lights or ignition sources.<br>Store in a cool, dry, well-ventilated area.  |

### Conditions for safe storage, including any incompatibilities

|                                |   |
|--------------------------------|---|
| <b>Suitable container</b>      | Metal can or drum<br>Packaging as recommended by manufacturer.<br>Check all containers are clearly labelled and free from leaks.  |
| <b>Storage incompatibility</b> | Traces of benzene, a carcinogen, may form when silicones are heated in air above 230 degrees C. Concentrated acids and bases cause degradation of polymer. Boiling water may soften and weaken material.<br><b>CARE:</b> Water in contact with heated material may cause foaming or a steam explosion with possible severe burns from wide scattering of hot material. Resultant overflow of containers may result in fire.<br>Avoid reaction with oxidising agents |

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)


INGREDIENT DATA

Not Available

EMERGENCY LIMITS

| Ingredient                    | Material name  | TEEL-1        | TEEL-2   | TEEL-3    |
|-------------------------------|--|---------------|----------|-----------|
| sodium dioctyl sulfosuccinate | Dioctyl sodium sulfosuccinate; (Di-(2-ethylhexyl) sodium sulfosuccinate) | 5.7 mg/m3     | 63 mg/m3 | 380 mg/m3 |
| Ingredient                    | Original IDLH  | Revised IDLH  |          |           |
| sodium dioctyl sulfosuccinate | Not Available  | Not Available |          |           |
| polyglycerol oleate           | Not Available  | Not Available |          |           |

#### Exposure controls

|   |  |
|---|--|
| <b>Appropriate engineering controls</b> | Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:<br>Process controls which involve changing the way a job activity or process is done to reduce the risk.<br>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.   |
| <b>Personal protection</b>              |   |
| <b>Eye and face protection</b>          | Safety glasses with side shields.<br>Chemical goggles.<br>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.  |
| <b>Skin protection</b>                  | See Hand protection below  |
| <b>Hands/feet protection</b>            | Wear chemical protective gloves, e.g. PVC.<br>Wear safety footwear or safety gumboots, e.g. Rubber<br><b>NOTE:</b><br>The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.<br>Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.<br>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.<br>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.<br>Personal hygiene is a key element of effective hand care. |
| <b>Body protection</b>                  | See Other protection below   |
| <b>Other protection</b>                 | Overalls.<br>P.V.C. apron.<br>Barrier cream.   |
| <b>Thermal hazards</b>                  | Not Available  |

#### Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator  |
|------------------------------------|----------------------|----------------------|-------------------------|
| up to 10 x ES                      | A-AUS P2             | -                    | A-PAPR-AUS / Class 1 P2 |
| up to 50 x ES                      | -                    | A-AUS / Class 1 P2   | -                       |
| up to 100 x ES                     | -                    | A-2 P2               | A-PAPR-2 P2 ^           |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

|   |   |  |                |
|---|---|--|----------------|
| <b>Appearance</b>                                   | White liquid with a woody odour; miscible with water. |  |                |
| <b>Physical state</b>                               | Liquid  | <b>Relative density (Water = 1)</b>            | 1.00           |
| <b>Odour</b>  | Not Available   | <b>Partition coefficient n-octanol / water</b> | Not Available  |
| <b>Odour threshold</b>                              | Not Available   | <b>Auto-ignition temperature (°C)</b>          | 21             |
| <b>pH (as supplied)</b>                             | 9.0 @ 21C   | <b>Decomposition temperature</b>               | Not Available  |
| <b>Melting point / freezing point (°C)</b>          | Not Available   | <b>Viscosity (cSt)</b>                         | Not Available  |
| <b>Initial boiling point and boiling range (°C)</b> | 100   | <b>Molecular weight (g/mol)</b>                | Not Applicable |
| <b>Flash point (°C)</b>                             | 216 (PMCC)  | <b>Taste</b>                                   | Not Available  |

|                                  |                |   |               |
|----------------------------------|----------------|---|---------------|
| <b>Evaporation rate</b>          | <1             | <b>Explosive properties</b>             | Not Available |
| <b>Flammability</b>              | Not Applicable | <b>Oxidising properties</b>             | Not Available |
| <b>Upper Explosive Limit (%)</b> | Not Available  | <b>Surface Tension (dyn/cm or mN/m)</b> | Not Available |
| <b>Lower Explosive Limit (%)</b> | Not Available  | <b>Volatile Component (%vol)</b>        | Not Available |
| <b>Vapour pressure (kPa)</b>     | Not Available  | <b>Gas group</b>                        | Not Available |
| <b>Solubility in water (g/L)</b> | Miscible       | <b>pH as a solution (1%)</b>            | Not Available |
| <b>Vapour density (Air = 1)</b>  | >1             | <b>VOC g/L</b>                          | Not Available |

## SECTION 10 STABILITY AND REACTIVITY

|   |   |
|---|---|
| <b>Reactivity</b>                         | See section 7   |
| <b>Chemical stability</b>                 | <p>Silicone fluids are stable under normal storage conditions.<br/> Hazardous polymerisation will not occur.<br/> At temperatures &gt; 150 C, silicones can slowly react with the oxygen in air.<br/> When heated &gt; 300 C, silicones can slowly depolymerise to volatile siloxanes whether or not air is present.<br/> Unstable in the presence of incompatible materials.<br/> Product is considered stable.<br/> Hazardous polymerisation will not occur.<br/> Presence of heat source and ignition source</p> |
| <b>Possibility of hazardous reactions</b> | See section 7   |
| <b>Conditions to avoid</b>                | See section 7   |
| <b>Incompatible materials</b>             | See section 7   |
| <b>Hazardous decomposition products</b>   | See section 5   |

## SECTION 11 TOXICOLOGICAL INFORMATION

### Information on toxicological effects

|                     |   |
|---------------------|---|
| <b>Inhaled</b>      | <p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.<br/> Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.<br/> There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.<br/> Vapours of silicones are generally fairly well tolerated, however very high concentrations can cause death within minutes due to respiratory failure. At high temperatures, the fumes and oxidation products can be irritating and toxic and can cause depression leading to death in very high doses.<br/> Inhaling high concentrations of mixed hydrocarbons can cause narcosis, with nausea, vomiting and lightheadedness. Low molecular weight (C2-C12) hydrocarbons can irritate mucous membranes and cause incoordination, giddiness, nausea, vertigo, confusion, headache, appetite loss, drowsiness, tremors and stupor.<br/> Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.</p> |
| <b>Ingestion</b>    | <p>Accidental ingestion of the material may be damaging to the health of the individual.<br/> Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)<br/> Silicone fluids do not have a high acute toxicity. They may have a laxative effect and produce central nervous system depression.<br/> Ingestion of petroleum hydrocarbons can irritate the pharynx, oesophagus, stomach and small intestine, and cause swellings and ulcers of the mucous. Symptoms include a burning mouth and throat; larger amounts can cause nausea and vomiting, narcosis, weakness, dizziness, slow and shallow breathing, abdominal swelling, unconsciousness and convulsions.</p>  |
| <b>Skin Contact</b> | <p>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.<br/> Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.<br/> There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.<br/> Low molecular weight silicone fluids may exhibit solvent action and may produce skin irritation.<br/> Open cuts, abraded or irritated skin should not be exposed to this material<br/> The material may accentuate any pre-existing dermatitis condition<br/> Excessive use or prolonged contact may lead to defatting, drying and irritation of sensitive skin</p>   |
| <b>Eye</b>          | <p>Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals. Prolonged eye contact may cause inflammation characterised by a temporary redness of the conjunctiva (similar to windburn).<br/> Eye exposure to silicone fluids causes temporary irritation of the conjunctiva. Injection into the specific structures of the eye, however, causes corneal scarring, permanent eye damage, allergic reactions and cataract, and may lead to blindness.<br/> Direct eye contact with petroleum hydrocarbons can be painful, and the corneal epithelium may be temporarily damaged. Aromatic species can cause irritation and excessive tear secretion.<br/> Non-ionic surfactants can cause numbing of the cornea, which masks discomfort normally caused by other agents and leads to corneal injury. Irritation varies depending on the duration of contact, the nature and concentration of the surfactant.</p>   |
| <b>Chronic</b>      | <p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.<br/> Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin.<br/> Oil may contact the skin or be inhaled. Extended exposure can lead to eczema, inflammation of hair follicles, pigmentation of the face and warts on the soles of the feet.</p>  |

|                                      |   |                                   |
|--------------------------------------|---|-----------------------------------|
| <b>Meguiar's G41 - Natural Shine</b> | <b>TOXICITY</b>                                 | <b>IRRITATION</b>                 |
|                                      | Not Available                                   | Not Available                     |
| <b>sodium dioctyl sulfosuccinate</b> | <b>TOXICITY</b>                                 | <b>IRRITATION</b>                 |
|                                      | Dermal (rabbit) LD50: 2525 mg/kg <sup>[1]</sup> | Eye (rabbit): 0.250 mg - mild     |
|                                      | Oral (rat) LD50: >1320 mg/kg <sup>[1]</sup>     | Eye (rabbit): 1% - SEVERE         |
|                                      |   | Skin (rabbit): 10 mg/24h-moderate |

|                |  |
|----------------|--|
| <b>Legend:</b> | 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances |
|----------------|--|

|  |  |
|--|--|
| <b>Meguiar's G41 - Natural Shine</b>                           | The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.<br>Siloxanes may impair liver and hormonal function, as well as the lung and kidney. They have not been found to be irritating to the skin and eyes. They may potentially cause cancer (tumours of the womb in females) and may cause impaired fertility or infertility.                           |
| <b>SODIUM DIOCTYL SULFOSUCCINATE</b>                           | The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.<br>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.<br>Structural changes in blood vessels recorded.  |
| <b>POLYGLYCEROL OLEATE</b>                                     | Group E aliphatic esters (polyol esters) are stable against oxidation and elimination, and may be used as synthetic lubricants for motor oil, jet engines, refrigeration lubricants, hydraulic fluids, industrial oven chain oils, high temperature greases, fire resistant transformer coolants and turbine engines. They may cause increase in kidney weight in the male rat but exhibits low acute/chronic effect with respect to reproduction and gene damage. |
| <b>Meguiar's G41 - Natural Shine &amp; POLYGLYCEROL OLEATE</b> | No significant acute toxicological data identified in literature search.   |

|  |                                 |
|--|---------------------------------|
| <b>Acute Toxicity</b>                    | <b>Carcinogenicity</b>          |
| <b>Skin Irritation/Corrosion</b>         | <b>Reproductivity</b>           |
| <b>Serious Eye Damage/Irritation</b>     | <b>STOT - Single Exposure</b>   |
| <b>Respiratory or Skin sensitisation</b> | <b>STOT - Repeated Exposure</b> |
| <b>Mutagenicity</b>                      | <b>Aspiration Hazard</b>        |

**Legend:**

- Data available but does not fill the criteria for classification
- Data required to make classification available
- Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

### Toxicity

| Ingredient                    | Endpoint   | Test Duration (hr) | Species                       | Value      | Source |
|-------------------------------|--|--------------------|-------------------------------|------------|--------|
| sodium dioctyl sulfosuccinate | LC50   | 96                 | Fish                          | =12.5mg/L  | 1      |
| sodium dioctyl sulfosuccinate | EC50   | 48                 | Crustacea                     | 6.6mg/L    | 2      |
| sodium dioctyl sulfosuccinate | EC50   | 72                 | Algae or other aquatic plants | 39.3mg/L   | 2      |
| sodium dioctyl sulfosuccinate | BCF  | 72                 | Fish                          | 0.0055mg/L | 4      |
| sodium dioctyl sulfosuccinate | EC50   | 48                 | Crustacea                     | 10.2mg/L   | 2      |
| sodium dioctyl sulfosuccinate | NOEC   | 96                 | Fish                          | =12.5mg/L  | 1      |
| <b>Legend:</b>                | Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data |                    |                               |            |        |

**DO NOT** discharge into sewer or waterways.

### Persistence and degradability

| Ingredient | Persistence: Water/Soil               | Persistence: Air                      |
|------------|---------------------------------------|---------------------------------------|
|            | No Data available for all ingredients | No Data available for all ingredients |

### Bioaccumulative potential

| Ingredient                    | Bioaccumulation  |
|-------------------------------|------------------|
| sodium dioctyl sulfosuccinate | LOW (BCF = 3.78) |

### Mobility in soil

| Ingredient | Mobility                              |
|------------|---------------------------------------|
|            | No Data available for all ingredients |

## SECTION 13 DISPOSAL CONSIDERATIONS

### Waste treatment methods

|                                     |  |
|-------------------------------------|--|
| <b>Product / Packaging disposal</b> | Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.<br>A Hierarchy of Controls seems to be common - the user should investigate:<br>Reduction<br>Reuse<br>Recycling<br>Disposal (if all else fails)<br>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. |
|-------------------------------------|--|

**DO NOT allow wash water from cleaning or process equipment to enter drains.**  
It may be necessary to collect all wash water for treatment before disposal.  
In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.  
Where in doubt contact the responsible authority.  
Recycle wherever possible or consult manufacturer for recycling options.  
Consult State Land Waste Authority for disposal.  
Bury or incinerate residue at an approved site.  
Recycle containers if possible, or dispose of in an authorised landfill.

## SECTION 14 TRANSPORT INFORMATION

### Labels Required

|                  |                |
|------------------|----------------|
| Marine Pollutant | NO             |
| HAZCHEM          | Not Applicable |

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

**SODIUM DIOCTYL SULFOSUCCINATE(577-11-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Inventory of Chemical Substances (AICS)

**POLYGLYCEROL OLEATE(9007-48-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Inventory of Chemical Substances (AICS)

| National Inventory            | Status   |
|-------------------------------|--|
| Australia - AICS              | Y  |
| Canada - DSL                  | Y  |
| Canada - NDSL                 | N (polyglycerol oleate; sodium dioctyl sulfosuccinate)   |
| China - IECSC                 | Y  |
| Europe - EINEC / ELINCS / NLP | N (polyglycerol oleate)  |
| Japan - ENCS                  | N (polyglycerol oleate)  |
| Korea - KECI                  | Y  |
| New Zealand - NZIoC           | Y  |
| Philippines - PICCS           | Y  |
| USA - TSCA                    | Y  |
| <b>Legend:</b>                | Y = All ingredients are on the inventory<br>N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

## SECTION 16 OTHER INFORMATION

### Other information

#### Ingredients with multiple cas numbers

| Name                          | CAS No  |
|-------------------------------|---|
| sodium dioctyl sulfosuccinate | 577-11-7, 53023-94-2, 51910-13-5, 52624-44-9, 59030-04-5, 60202-21-3, 66812-62-2, 67924-68-9, 75418-10-9, 76689-26-4, 78207-03-1, 105956-73-8, 106396-28-5, 110162-65-7, 113255-61-1, 130390-93-1, 135843-72-0, 138893-51-3, 141092-35-5, 201816-76-4, 202352-75-8, 209122-63-4, 209453-97-4, 835616-33-6 |
| polyglycerol oleate           | 9007-48-1, 9009-31-8  |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:  
[www.chemwatch.net](http://www.chemwatch.net)

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average  
PC—STEL: Permissible Concentration-Short Term Exposure Limit  
IARC: International Agency for Research on Cancer  
ACGIH: American Conference of Governmental Industrial Hygienists  
STEL: Short Term Exposure Limit  
TEEL: Temporary Emergency Exposure Limit.  
IDLH: Immediately Dangerous to Life or Health Concentrations  
OSF: Odour Safety Factor  
NOAEL :No Observed Adverse Effect Level  
LOAEL: Lowest Observed Adverse Effect Level  
TLV: Threshold Limit Value  
LOD: Limit Of Detection  
OTV: Odour Threshold Value

BCF: BioConcentration Factors  
BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.