

MEGUIAR'S MC205 - MOTORCYCLE PLASTIC POLISH

Chemwatch Material Safety Data Sheet
Issue Date: 15-Jan-2008
NA317EC

CHEMWATCH 03-0109
Version No:1
CD 2007/4 Page 1 of 14

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

MEGUIAR'S MC205 - MOTORCYCLE PLASTIC POLISH

SYNONYMS

"burnishing compound"

PRODUCT USE

Polishing agent. Burnishing compound.

SUPPLIER

Company: MotorActive
Address:
35 Slough Business Park
Holker St, Silverwater
NSW, 2128
AUS
Telephone: +61 2 9737 9422
Telephone: 1800 347 570
Fax: +61 2 9737 9414

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

COMBUSTIBLE LIQUID, regulated under AS1940 for Bulk Storage purposes only.

POISONS SCHEDULE

None

RISK

In use may form flammable/ explosive vapour- air mixture.
Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child.
HARMFUL- May cause lung damage if swallowed.
Inhalation and/or ingestion may produce health damage*.

Cumulative effects may result following exposure*.
Limited evidence of a carcinogenic effect*.

Repeated exposure potentially causes skin dryness and cracking*.
Vapours potentially cause drowsiness and dizziness*.

* (limited evidence).

SAFETY

Do not breathe gas/fumes/vapour/spray.

Use only in well ventilated areas.

Keep container in a well ventilated place.

Avoid exposure - obtain special instructions before use.

To clean the floor and all objects contaminated by this material use water and detergent.

Keep container tightly closed.

Keep away from food drink and animal feeding stuffs.

Take off immediately all contaminated clothing.

If swallowed IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).

continued...

MEGUIAR'S MC205 - MOTORCYCLE PLASTIC POLISH

Chemwatch Material Safety Data Sheet

Issue Date: 15-Jan-2008

NA317EC

CHEMWATCH 03-0109

Version No:1

CD 2007/4 Page 2 of 14

Section 2 - HAZARDS IDENTIFICATION

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
naphtha petroleum, isoparaffin, hydrotreated	64742-48-9.	5-15
solvent naphtha petroleum, medium aliphatic	64742-88-7	2-10
aluminium oxide	1344-28-1.	2-10
distillates, petroleum, light, hydrotreated	64742-47-8	2-10
distillates, petroleum, middle, hydrotreated	64742-46-7.	1-5

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
 - If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
 - Observe the patient carefully.
 - Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
 - Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
 - Seek medical advice.
- Avoid giving milk or oils.
Avoid giving alcohol.
- If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - If pain persists or recurs seek medical attention.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin or hair contact occurs:
- Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration

continued...

MEGUIAR'S MC205 - MOTORCYCLE PLASTIC POLISH

Chemwatch Material Safety Data Sheet

Issue Date: 15-Jan-2008

NA317EC

CHEMWATCH 03-0109

Version No:1

CD 2007/4 Page 3 of 14

Section 4 - FIRST AID MEASURES

into the lungs may be delayed up to 48 hours.

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

WARNING: In use may form flammable/ explosive vapour-air mixtures.

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Combustion products include: carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

continued...

MEGUIAR'S MC205 - MOTORCYCLE PLASTIC POLISH

Chemwatch Material Safety Data Sheet

Issue Date: 15-Jan-2008

NA317EC

CHEMWATCH 03-0109

Version No:1

CD 2007/4 Page 4 of 14

Section 5 - FIRE FIGHTING MEASURES

HAZCHEM: None

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

MAJOR SPILLS

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- Electrostatic discharge may be generated during pumping - this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/sec until fill pipe submerged to twice its diameter, then ≤ 7 m/sec).
- Avoid splash filling.
- Do NOT use compressed air for filling discharging or handling operations.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.

continued...

MEGUIAR'S MC205 - MOTORCYCLE PLASTIC POLISH

Chemwatch Material Safety Data Sheet

Issue Date: 15-Jan-2008

NA317EC

CHEMWATCH 03-0109

Version No:1

CD 2007/4 Page 5 of 14

Section 7 - HANDLING AND STORAGE

- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA mg/m ³
Australia Exposure Standards	aluminium oxide (Aluminium oxide (a))	10

The following materials had no OELs on our records

- naphtha petroleum, isoparaffin, hydrotreated: CAS:64742- 48- 9
- solvent naphtha petroleum, medium aliphatic: CAS:64742- 88- 7
- distillates, petroleum, light, hydrotreated: CAS:64742- 47- 8
- distillates, petroleum, middle, hydrotreated: CAS:64742- 46- 7

MATERIAL DATA

Not available. Refer to individual constituents.

INGREDIENT DATA

DISTILLATES, PETROLEUM, LIGHT, HYDROTREATED:
NAPHTHA PETROLEUM, ISOPARAFFIN, HYDROTREATED:
SOLVENT NAPHTHA PETROLEUM, MEDIUM ALIPHATIC:
for petroleum distillates:
CEL TWA: 500 ppm, 2000 mg/m³ (compare OSHA TWA).

DISTILLATES, PETROLEUM, LIGHT, HYDROTREATED:
NAPHTHA PETROLEUM, ISOPARAFFIN, HYDROTREATED:
SOLVENT NAPHTHA PETROLEUM, MEDIUM ALIPHATIC:

continued...

MEGUIAR'S MC205 - MOTORCYCLE PLASTIC POLISH

Chemwatch Material Safety Data Sheet

Issue Date: 15-Jan-2008

NA317EC

CHEMWATCH 03-0109

Version No:1

CD 2007/4 Page 6 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

DISTILLATES, PETROLEUM, LIGHT, HYDROTREATED:

DISTILLATES, PETROLEUM, MIDDLE, HYDROTREATED:

Human exposure to oil mist alone has not been demonstrated to cause health effects except at levels above 5 mg/m³ (this applies to particulates sampled by a method that does not collect vapour). It is not advisable to apply this standard to oils containing unknown concentrations and types of additive.

NAPHTHA PETROLEUM, ISOPARAFFIN, HYDROTREATED:

REL TWA: 400 ppm [EXXON]

SOLVENT NAPHTHA PETROLEUM, MEDIUM ALIPHATIC:

Naphthas of this type produce central nervous system depression and are mild irritants of the eyes and upper respiratory tract. The carcinogenic potential of middle petroleum distillates is recognised and is related to the content of polynuclear aromatic hydrocarbons

(PAHs). The TLV is thought to be protective against the acute effects of upper respiratory tract and eye irritation and chronic systemic effects.

CAUTION: This substance has been classified by the ACGIH as A3
Animal carcinogen (at relatively high doses).

NOTE L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346. European Union (EU) List of Dangerous Substances (Annex I) - up to the 29th ATP.

CEL TWA: 100 ppm, 525 mg/m³ [Manufacturer]

ALUMINIUM OXIDE:

The experimental and clinical data indicate that aluminium oxide acts as an "inert" material when inhaled and seems to have little effect on the lungs nor does it produce significant organic disease or toxic effects when exposures are kept under reasonable control.

[Documentation of the Threshold Limit Values], ACGIH, Sixth Edition

DISTILLATES, PETROLEUM, LIGHT, HYDROTREATED:

CEL TWA: 300 ppm, 2100 mg/m³

continued...

MEGUIAR'S MC205 - MOTORCYCLE PLASTIC POLISH

Chemwatch Material Safety Data Sheet

Issue Date: 15-Jan-2008

NA317EC

CHEMWATCH 03-0109

Version No:1

CD 2007/4 Page 7 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION

EYE

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Suitability and durability of glove type is dependent on usage. Factors such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity,

are important in the selection of gloves.

Wear chemical protective gloves, eg. PVC.

Wear safety footwear or safety gumboots, eg. Rubber.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

RESPIRATOR

Respiratory protection may be required when ANY "Worst Case" vapour-phase concentration is exceeded (see Computer Prediction in "Exposure Standards").

Protection Factor (Min)	Half- Face Respirator	Full- Face Respirator
5 x ES	A- P- - AUS A- P- - PAPR- AUS	-
25 x ES	Air- line*	A- P- - 2 A- P- - PAPR- 2
50 x ES	-	A- P- - 3
50+ x ES	-	Air- line**

* - Continuous-flow; ** - Continuous-flow or positive pressure demand

^ - Full-face.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type

continued...

MEGUIAR'S MC205 - MOTORCYCLE PLASTIC POLISH

Chemwatch Material Safety Data Sheet
Issue Date: 15-Jan-2008
NA317EC

CHEMWATCH 03-0109
Version No:1
CD 2007/4 Page 8 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Off white liquid with a pleasant odour; partly mixes with water.

PHYSICAL PROPERTIES

Liquid.

Molecular Weight: Not Applicable

Melting Range (°C): Not Available

Solubility in water (g/L): Partly Miscible

pH (1% solution): Not Available

Volatile Component (%vol): Not Available

Relative Vapour Density (air=1): >1

Lower Explosive Limit (%): Not Applicable

Autoignition Temp (°C): Not Applicable

State: Liquid

Boiling Range (°C): 177

Specific Gravity (water= 1): 0.96

pH (as supplied): 8

Vapour Pressure (kPa): Not Available

Evaporation Rate: Not Available

Flash Point (°C): 93

Upper Explosive Limit (%): Not Applicable

Decomposition Temp (°C): Not Available

Viscosity: Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result.
(ICSC13733).

Accidental ingestion of the material may be damaging to the health of the individual.

Ingestion of petroleum hydrocarbons may produce irritation of the pharynx, oesophagus, stomach and small intestine with oedema and mucosal ulceration resulting; symptoms include a burning sensation in the mouth and throat. Large amounts may produce narcosis with nausea and vomiting, weakness or dizziness, slow and shallow respiration, swelling of the abdomen, unconsciousness and convulsions. Myocardial injury may produce arrhythmias, ventricular fibrillation and electrocardiographic changes. Central nervous system depression may also occur. Light aromatic hydrocarbons produce a warm, sharp, tingling sensation on contact with taste buds and may anaesthetise the tongue. Aspiration into the lungs may produce coughing, gagging and a chemical pneumonitis with pulmonary oedema and haemorrhage.

continued...

MEGUIAR'S MC205 - MOTORCYCLE PLASTIC POLISH

Chemwatch Material Safety Data Sheet

Issue Date: 15-Jan-2008

NA317EC

CHEMWATCH 03-0109

Version No:1

CD 2007/4 Page 9 of 14

Section 11 - TOXICOLOGICAL INFORMATION

EYE

Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

SKIN

The liquid may be miscible with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives .

Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.

The material may accentuate any pre-existing dermatitis condition.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

Inhalation hazard is increased at higher temperatures.

If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.

CHRONIC HEALTH EFFECTS

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Serious damage (clear functional disturbance or morphological change which may have toxicological significance) is likely to be caused by repeated or prolonged exposure. As a rule the material produces, or contains a substance which produces severe lesions. Such damage may become apparent following direct application in subchronic (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity tests.

Exposure to the material may cause concerns for humans owing to possible developmental toxic effects, generally on the basis that results in appropriate animal studies provide strong suspicion of developmental toxicity in the absence of signs of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not a secondary non-specific consequence of other toxic effects.

On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Repeated application of mildly hydrotreated oils (principally paraffinic), to mouse skin, induced skin tumours; no tumours were induced with severely hydrotreated oils.

Repeated or prolonged exposure to mixed hydrocarbons may produce narcosis with dizziness, weakness, irritability, concentration and/or memory loss, tremor in the fingers and tongue, vertigo, olfactory disorders, constriction of visual field, paraesthesias of the extremities, weight loss and anaemia and degenerative changes in the liver and kidney.

Chronic exposure by petroleum workers, to the lighter hydrocarbons, has been associated with visual disturbances, damage to the central nervous system, peripheral neuropathies (including numbness and paraesthesias), psychological and neurophysiological deficits, bone marrow toxicities (including hypoplasia possibly due to benzene) and hepatic and renal involvement. Chronic dermal exposure to petroleum hydrocarbons may result in defatting which produces localised dermatoses. Surface cracking and erosion may also increase susceptibility to infection by microorganisms. One epidemiological study of petroleum refinery workers has reported elevations in standard mortality ratios for skin cancer along with a dose-response relationship indicating an association between routine

continued...

MEGUIAR'S MC205 - MOTORCYCLE PLASTIC POLISH

Chemwatch Material Safety Data Sheet

Issue Date: 15-Jan-2008

NA317EC

CHEMWATCH 03-0109

Version No:1

CD 2007/4 Page 10 of 14

Section 11 - TOXICOLOGICAL INFORMATION

workplace exposure to petroleum or one of its constituents and skin cancer, particularly melanoma. Other studies have been unable to confirm this finding.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

NAPHTHA PETROLEUM, ISOPARAFFIN, HYDROTREATED:

No significant acute toxicological data identified in literature search.

SOLVENT NAPHTHA PETROLEUM, MEDIUM ALIPHATIC:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: >25 ml/kg

Dermal (rabbit) LD50: >4 ml/kg [CCINFO]

The material may produce severe irritation to the eye causing pronounced inflammation.

Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

IRRITATION

Nil Reported

ALUMINIUM OXIDE:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

No significant acute toxicological data identified in literature search.

DISTILLATES, PETROLEUM, LIGHT, HYDROTREATED:

No significant acute toxicological data identified in literature search.

DISTILLATES, PETROLEUM, MIDDLE, HYDROTREATED:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

typical for isoparaffinic hydrocarbons:

Inhalation (rat) LC50: 3400 ppm/4H None reported [EXXON]

isoparaffinic hydrocarbon:

Oral (rat) LD50 : >8000 mg/kg

Dermal (rat) LD50: >4000 mg/kg

IRRITATION

[CCINFO-Shell]

Section 12 - ECOLOGICAL INFORMATION

The lower molecular weight hydrocarbons are expected to form a "slick" on the surface of waters after release in calm sea conditions. This is expected to evaporate and enter the atmosphere where it will be degraded through reaction with hydroxy radicals.

Some of the material will become associated with benthic sediments, and it is likely to be spread over a fairly wide area of sea floor. Marine sediments may be either aerobic or anaerobic. The material, in probability, is biodegradable, under aerobic conditions (isomerised olefins and alkenes show variable results). Evidence also suggests that the hydrocarbons may be degradable under anaerobic conditions although such degradation in benthic sediments may be a relatively slow process.

Under aerobic conditions the material will degrade to water and carbon dioxide, while

continued...

MEGUIAR'S MC205 - MOTORCYCLE PLASTIC POLISH

Chemwatch Material Safety Data Sheet

Issue Date: 15-Jan-2008

NA317EC

CHEMWATCH 03-0109

Version No:1

CD 2007/4 Page 11 of 14

Section 12 - ECOLOGICAL INFORMATION

under anaerobic processes it will produce water, methane and carbon dioxide.

Based on test results, as well as theoretical considerations, the potential for bioaccumulation may be high. Toxic effects are often observed in species such as blue mussel, daphnia, freshwater green algae, marine copepods and amphipods.

Drinking Water Standards:

hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

NAPHTHA PETROLEUM, ISOPARAFFIN, HYDROTREATED:

The lower molecular weight hydrocarbons are expected to form a "slick" on the surface of waters after release in calm sea conditions. This is expected to evaporate and enter the atmosphere where it will be degraded through reaction with hydroxy radicals.

Some of the material will become associated with benthic sediments, and it is likely to be spread over a fairly wide area of sea floor. Marine sediments may be either aerobic or anaerobic. The material, in probability, is biodegradable, under aerobic conditions (isomerised olefins and alkenes show variable results). Evidence also suggests that the hydrocarbons may be degradable under anaerobic conditions although such degradation in benthic sediments may be a relatively slow process.

Under aerobic conditions the material will degrade to water and carbon dioxide, while under anaerobic processes it will produce water, methane and carbon dioxide.

Based on test results, as well as theoretical considerations, the potential for bioaccumulation may be high. Toxic effects are often observed in species such as blue mussel, daphnia, freshwater green algae, marine copepods and amphipods.

Drinking Water Standards:

hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

SOLVENT NAPHTHA PETROLEUM, MEDIUM ALIPHATIC:

The lower molecular weight hydrocarbons are expected to form a "slick" on the surface of waters after release in calm sea conditions. This is expected to evaporate and enter the atmosphere where it will be degraded through reaction with hydroxy radicals.

Some of the material will become associated with benthic sediments, and it is likely to be spread over a fairly wide area of sea floor. Marine sediments may be either aerobic or anaerobic. The material, in probability, is biodegradable, under aerobic conditions (isomerised olefins and alkenes show variable results). Evidence also suggests that the hydrocarbons may be degradable under anaerobic conditions although such degradation in benthic sediments may be a relatively slow process.

Under aerobic conditions the material will degrade to water and carbon dioxide, while under anaerobic processes it will produce water, methane and carbon dioxide.

Based on test results, as well as theoretical considerations, the potential for bioaccumulation may be high. Toxic effects are often observed in species such as blue mussel, daphnia, freshwater green algae, marine copepods and amphipods.

Drinking Water Standards:

hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

DISTILLATES, PETROLEUM, LIGHT, HYDROTREATED:

The lower molecular weight hydrocarbons are expected to form a "slick" on the surface of waters after release in calm sea conditions. This is expected to evaporate and enter the atmosphere where it will be degraded through reaction with hydroxy radicals.

continued...

MEGUIAR'S MC205 - MOTORCYCLE PLASTIC POLISH

Chemwatch Material Safety Data Sheet

Issue Date: 15-Jan-2008

NA317EC

CHEMWATCH 03-0109

Version No:1

CD 2007/4 Page 12 of 14

Section 12 - ECOLOGICAL INFORMATION

Some of the material will become associated with benthic sediments, and it is likely to be spread over a fairly wide area of sea floor. Marine sediments may be either aerobic or anaerobic. The material, in probability, is biodegradable, under aerobic conditions (isomerised olefins and alkenes show variable results). Evidence also suggests that the hydrocarbons may be degradable under anaerobic conditions although such degradation in benthic sediments may be a relatively slow process.

Under aerobic conditions the material will degrade to water and carbon dioxide, while under anaerobic processes it will produce water, methane and carbon dioxide.

Based on test results, as well as theoretical considerations, the potential for bioaccumulation may be high. Toxic effects are often observed in species such as blue mussel, daphnia, freshwater green algae, marine copepods and amphipods.

Drinking Water Standards:

hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

Section 13 - DISPOSAL CONSIDERATIONS

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction,
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.


DO NOT allow wash water from cleaning or process equipment to enter drains.

It may be necessary to collect all wash water for treatment before disposal.

In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority.

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: COMBUSTIBLE LIQUID, regulated under AS1940 for Bulk Storage purposes only.
HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA,

continued...

MEGUIAR'S MC205 - MOTORCYCLE PLASTIC POLISH

Chemwatch Material Safety Data Sheet

Issue Date: 15-Jan-2008

NA317EC

CHEMWATCH 03-0109

Version No:1

CD 2007/4 Page 13 of 14

Section 14 - TRANSPORTATION INFORMATION

IMDG

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: None

REGULATIONS

Meguiar's MC205 - Motorcycle Plastic Polish (CAS: None):
No regulations applicable

naphtha petroleum, isoparaffin, hydrotreated (CAS: 64742-48-9) is found on the following regulatory lists;

Australia High Volume Industrial Chemical List (HVICL)
Australia Inventory of Chemical Substances (AICS)
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals

solvent naphtha petroleum, medium aliphatic (CAS: 64742-88-7) is found on the following regulatory lists;

Australia High Volume Industrial Chemical List (HVICL)
Australia Inventory of Chemical Substances (AICS)
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals

aluminium oxide (CAS: 1344-28-1) is found on the following regulatory lists;

Australia Exposure Standards
Australia High Volume Industrial Chemical List (HVICL)
Australia Inventory of Chemical Substances (AICS)
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals

distillates, petroleum, light, hydrotreated (CAS: 64742-47-8) is found on the following regulatory lists;

Australia High Volume Industrial Chemical List (HVICL)
Australia Inventory of Chemical Substances (AICS)
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals

distillates, petroleum, middle, hydrotreated (CAS: 64742-46-7) is found on the following regulatory lists;

Australia High Volume Industrial Chemical List (HVICL)
Australia Inventory of Chemical Substances (AICS)
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

EXPOSURE STANDARD FOR MIXTURES

"Worst Case" computer-aided prediction of vapour components/concentrations:

Composite Exposure Standard for Mixture (TWA) (mg/m³): 840 mg/m³

If the breathing zone concentration of ANY of the components listed below is exceeded,

"Worst Case" considerations deem the individual to be overexposed.

Component Breathing Zone ppm Breathing Zone mg/m³ Mixture Conc: (%).

Component	Breathing zone (ppm)	Breathing Zone (mg/m ³)	Mixture Conc (%)
solvent naphtha petroleum, medium aliphatic	80.00	420.0000	10.0
distillates, petroleum, light, hydrotreated	60.00	420.0000	10.0

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be

continued...

MEGUIAR'S MC205 - MOTORCYCLE PLASTIC POLISH

Chemwatch Material Safety Data Sheet

Issue Date: 15-Jan-2008

NA317EC

CHEMWATCH 03-0109

Version No:1

CD 2007/4 Page 14 of 14

Section 16 - OTHER INFORMATION

considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 15-Jan-2008

Print Date: 16-Jan-2008